



BXTR6438

Hydraulic Feed | Towable/Self-Contained (Electronic Controls)

Chipping Capacity	7" (17 cm)	On-Board Intelligence	P3 Pulse™
Chipper Type	Disc	Feed System	Hydraulic Roller Feed
Max. Feed Rate	129 fpm (39 mpm)	Engine	Vanguard® 40 hp (993 cc) EFI
Chipper Hopper Opening	25" x 34" (64 cm x 86 cm)	Chipper Infeed Opening	7" x 11" (18 cm x 28 cm)
Number of Chipper Knives	4	Rotor Diameter	30" (76 cm)
Rotor Weight	197 lbs (89 kg)	Discharge Chute Height	100" (255 cm)
Discharge Chute Rotation	360°	Drive System	Centrifugal Clutch, Belt Drive
Engine Speed	3600 RPM	Rotor Speed	1400 RPM
Tires	ST205/75R14	Hitch	2" Ladder Style Ball Coupler
Electric Brakes	No	Tongue Weight	221 lb
Total Weight	2225 lb (1009 kg)	Dimensions Open (LxWxH)	149" x 64" x 100" (378 cm x 163 cm x 255 cm)
Dimensions Folded	128" x 64" x 100" (326 cm x 255 cm)	Hydraulic Capacity	7 US gal (30 L) (LxWxH) cm x 163
Fuel Tank Capacity	9 US gal (34 L)		

Features

Adjustable Discharge Chute
Electric Start
Oversized Heavy Duty Rotor
Positional Discharge Deflector
Torflex® Suspension Axle

Built In Toolbox
Fold Up Feed Hopper - No Tools
Oversized Opening
Reversible Rotor Knives
Twig Breaker

Dual Active Rollers
Highway Towable
P3 Pulse
Safety Control Bar

Accessories

2-5/16" Ball Hitch
Reversible Rotor Knife

Ledger Knife
Spark Arrestor - Vanguard®

Ledger Knife Clearance Gauge

Price is subject to change without notice. Go to [WallensteinEquipment.com](https://www.wallensteinequipment.com) to see the current price, local availability, compatibility, videos, pictures, and more.